



[CONSUMER PRODUCTS HOME](#)

SEARCH

[DOWNLOAD LIBRARY](#)

[SUPPORT](#)

[WHERE TO BUY](#)

[PROMOTIONS](#)

[CONTACT CANON](#)

[CAMERAS](#)

[CAMCORDERS](#)

[PRINTERS](#)

[SCANNERS](#)

[MULTIFUNCTION](#)

[COPIERS & FAX](#)

[BINOCULARS](#)

[NETWORK VIDEO SOLUTIONS](#)

[PROJECTORS & VISUALIZERS](#)

[CALCULATORS](#)

[SUPPLIES & ACCESSORIES](#)

Consumer Products Home :: Support :: PowerShot A60 :: Specifications

Specifications

PowerShot A60



Type of Camera

Type of Camera Compact digital still camera with built-in flash and 3x Optical / 2.5x Digital / 7.5x Combined Zoom

Image Capture Device

Type 1/2.7 inch charge coupled device (CCD)

Total Pixels Approx. 2.0 Million

Effective Pixels 2.0 Million

Lens

Focal Length 5.4 - 16.2mm zoom lens (35mm film equivalent: 35 - 105mm)

Digital Zoom 2.5x

Focusing Range

Normal AF: 46cm/1.5 ft. - infinity
 Macro AF: 5 - 46cm/2.0 in. - 1.5 ft. (wide-angle), 26 - 46cm/10 in. - 1.5 ft. (telephoto)
 Manual focus: 5cm/2.0 in. - infinity (wide-angle), 26cm/10 in. - infinity (telephoto)

Autofocus System

Around most of picture area
 AF lock and Manual focus are available

Viewfinders

Optical Viewfinder

Real-image optical zoom viewfinder

LCD Monitor

1.5 inch low temperature polycrystalline silicon TFT color LCD

LCD Pixels

Approx. 78,000 pixels

LCD Coverage

100%

Aperture and Shutter

Maximum Aperture f/2.8 - 4.8

Shutter Speed

15 - 1/2,500 sec. Slow shutter speed of 1.3 sec. is only available in select modes

Exposure Control

Sensitivity AUTO/ISO 50/100/200/400 equivalent

Light Metering Method

Evaluative/Center-weighted average/Spot

Exposure Control Method

Program AE/Manual

Exposure Compensation

+/-2 EV in 1/3-stop increments

Auto Exposure Bracketing

Not Available

White Balance

White Balance Control

TTL Auto White Balance, Pre-set (Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, or Flash), or Custom

Flash

Built-in Flash

Operation Modes: Auto/ON/OFF, Red-Eye Reduction, Red-Eye Reduction ON/OFF

SHOP

SUPPORT

Download Library

Register Your Product

Request or Track a Repair

Find Supplies & Accessories

Choose Another Model ...

1 Select category

2 Select product type

3 Select model

Support Site Map

CANON ADVANTAGES



Flash Range WIDE: 46 - 4.2m
 TELE: 46 - 2.5m
 MACRO: 26 - 46cm (When sensitivity is set to ISO 100 equivalent)

Recycling Time Approx. 10 sec. or less

Flash Exposure Compensation Not Available

Shooting Specifications

Shooting Modes Auto, Creative (P, Av, Tv, M, Custom 1, Custom 2), Programmed Image Control Zone, Image (Portrait, Landscape, Night Scene, Stitch Assist, Movie)

Photo Effects Vivid, Neutral, Low Sharpening, Sepia and Black&White

Self-Timer Operates with approx. 2 sec. or approx 10 sec. count-down

Wireless Control Not Available

Continuous Shooting Approx. 2.6 frames/ sec.

Image Storage

Storage Media CompactFlash (CF) Card Type I

File Format Design rule for Camera File system (DCF*1)

Print Order Format Digital Print Order Format (DPOF) Version 1.1

Image Compression Still Image: JPEG (Exif 2.2 compliant)

JPEG Compression Mode SuperFine, Fine or Normal

Number of Recording Pixels 1600 x 1200 (Large), 1024 x 768 (Medium), 640 x 480 pixels (Small)
 Movie: 320 x 240 or 160 x 120

Number of Recordable Images

Menu Selection	File Size (KB)	Resolution (pixels)	8MB	16MB	32MB	64MB	128MB	256MB
Large / SuperFine	1,002	1,600 x 1,200	7	14	30	61	122	246
Large / Fine	558	1,600 x 1,200	13	26	54	109	219	440
Large / Normal	278	1,600 x 1,200	26	52	108	217	435	868
Medium / SuperFine	570	1,024 x 768	12	25	53	107	215	431
Medium / Fine	320	1,024 x 768	23	46	94	189	379	762
Medium / Normal	170	1,024 x 768	42	58	174	349	700	1,390
Small / SuperFine	249	640 x 480	29	58	120	241	482	962
Small / Fine	150	640 x 480	47	94	196	393	788	1,563
Small / Normal	84	640 x 480	83	165	337	676	1,355	2,720

Time of Recordable Movies

	Resolution (pixels)	8MB	16MB	32MB	64MB	128MB	256MB
Movie / High	320 x 240	21sec.	44sec.	91sec.	183 sec.	368sec.	735sec.
Movie / Low	160 x 120	58sec.	118sec.	242 sec.	486sec.	973 sec.	1,954sec.

Playback Specifications

Playback Modes File Single, Index (9 thumbnails), Magnification (2x to 10x), Movie, Slide Show

Erasing Specifications

Erase Modes Single Image, All Images, Movie: Part of movie, All movie

Interfaces

Computer Interface Universal Serial Bus (USB) (mini-B jack)

Video Out NTSC or PAL

Other CF card slot (accept type I and type II cards). Direct connection to Canon CP Printers and Direct Photo Printers (no computer required)

Power Supply

Power Source 1. Size AA Alkaline battery x4
2. Rechargeable size AA NiMH battery x4 (NB-1AH)
3. Compact Power Adapter (ACK-600)

Shooting Capacity Approx. 250 shots/Approx. 800 shots (LCD monitor ON)
Approx. 350 shots/Approx. 1000 shots (LCD monitor OFF)
(Alkaline battery/ NB-1AH)

Playback Time Approx. 280 min/Approx 280 min. (Alkaline battery/ NB-1AH)

Physical Specifications

Operating Temperature 32 - 104°F (0 - 40°C)

Operating Humidity 10 - 90%

Dimensions (W x H x D) 3.98 x 2.52 x 1.24 in./101.0 x 64.0 x 31.5mm (Excluding protrusions)

Weight Approx. 7.58 oz./215g (Camera body only)

Computer System Requirements

Mac Requirements Computer Model: Power Macintosh, PowerBook, iMac, eMac or iBook
OS: OS 9.0 â€ 9.2 or OSX 10.1 â€ 10.2.
CPU: PowerPC.
Interface: USB (Models with Apple genuine USB interface only).

PC Requirements Computer Model: IBM PC/AT compatible
OS: Microsoft Windows 98 (including Second Edition)/ Me/ 2000/ XP.
CPU: Pentium 150MHz or higher processor (Windows 98/ME/2000), Pentium 300MHz or higher processor (Windows XP).
Interface: USB (Windows 98/ Me/ 2000/ XP pre-install model only).

Note: *1 "DCF" is an abbreviation of "Design rule for Camera File system" standardized by Japan Electronics and Information Technology Industries Association (JEITA).

© 2005 Canon U.S.A., Inc. All rights reserved. Duplication in whole or in part without permission is prohibited. [Privacy Statement](#) :: [Terms of Use](#)